

Model	INV 5.0 TP	INV 6.0 TP	INV 8.0 TP	INV 10.0 TP	INV 12.0 TP	INV 15.0 TP	INV 18.0 TP	INV 20.0 TP	INV 25.0 TP
<b>Input ( DC )</b>									
Recommended max. PV Input Power	7500Wp	9000Wp	12000Wp	15000Wp	18000Wp	28500Wp	25500Wp	30000Wp	30000Wp
Max. PV Input voltage	1000V								
Min. Working Voltage	160 VDC						250 VDC		
Nominal PV Input voltage	850 VDC								
MPPT Voltage Range	160 - 850 VDC						200 - 850 VDC		
No. of Independent MPPT Inputs	1						2		
Default No. of PV Strings Per MPPT	2								
Max. PV Input Current	27A						26/26 A		34/26 A
Max. DC Short-Circuit Current	48A						34/34 A		46/34 A
<b>Output ( AC )</b>									
Nominal AC Output Power	5000W	6000W	8000W	10000W	12000W	15000W	18000W	20000W	25000W
Max. AC Output Power	5500 VA	6600 VA	8800 VA	11000 VA	13200 VA	16500 VA	19800 VA	22000 VA	27500 VA
Max. AC Output Current	10 A	12 A	15 A	17 A	20 A	23 A	25 A	30 A	36A
Nominal AC Output Voltage Range	50/60 Hz, 400 Vac								
AC Voltage Range	280 - 490 Vac								
Rated Grid Frequency/ Grid Frequency Range	50 Hz / 45 - 55 Hz, 60 Hz / 55 - 65 Hz								
Harmonic ( THD )	< 5 % ( At Rated Power )				< 1.5 % ( at rated power )				
Power Factor at Rated Power / Adjustable Power Factor	-1 / (Adjustable 0.8 leading - 0.8 lagging)								
<b>Efficiency</b>									
Max. Efficiency	98.20%		98.30%	97.40%		99.50%	98.50%		
MPPT Efficiency	99.90%								
<b>Protection</b>									
Grid Monitoring	Yes								
DC Reverse Polarity Protection	Yes								
Short-Circuit Protection	Yes								
Leakage Current Protection	Yes								
Surge Protection	Yes								
DC switch	Yes								
Anti Islanding/Overvoltage Protection	Yes								
Residual Current Protection	Yes								
<b>General Data</b>									
Dimensions ( W * H * D )	420 mm * 370 mm * 130 mm						520 mm * 510 mm * 160 mm		
Weight	16 kg				23 kg				
Mounting Method	Wall-Mounting Bracket								
Topology	Transformerless								
Degree of Protection	Ip65 According to IEC 60529								
Operating Ambient Temperature Range	-25°C - 60°C								
Allowable Relative Humidity Range (Non-Condensing)	0 - 95 %, No Condensation								
Cooling Method	Smart Cooling								
Max. Operating Altitude	3000m Without Power Derating								
Display	LCD								
Communication	WiFi Standard, RS485, GPRS								
DC Connection Type	Mc4 Compatible Connector								
Acoustic Noise Level (dB)	<30								
Warranty	8 Years								
<b>Standards and Compliance</b>									
Grid Compliance	CE-(EMC/LVD) : EN(IEC) 61000-1/-2/-3/; EN(IEC) 62109-1/-2, BIS, IEC 60068-2, IEC 61683:1999, IEC 61727:2004, IEC 62106:2014, IEC/EN 62109-1, IEC/EN 62109-2, IEC 61000								